



Front Loading Utensil Washer with Inbuilt Softener

UXS-10B



1 Water	2 Drain	3 Electric
22mm CONNECTION VIA 1.5 METRE FLEXIBLE HOSE, FEMALE TERMINATION. WATER SUPPLY 15°C TO 60°C (2° TO 8° CLARK MAX) @ 0.5 TO 10 BAR MAX. INITIAL TANK FILL 80 LITRES. RINSE WATER USAGE 4.1 LITRES PER CYCLE. MAX USAGE 123 LITRES PER HOUR. OUR MACHINES ARE SUPPLIED WITH CLASS 'AB' AIR GAP AS STANDARD. WATER SUPPLY TO HAVE INDEPENDENT ISOLATING VALVE.	DRAIN - 2 METRE FLEXIBLE HOSE TO A 40 mm TRAPPED STANDPIPE 800mm A.F.F.L.  FLOW RATE 30 LITRES PER MINUTE.	15.1kW 400/50/3 + N + E FUSED AT 25AMPS. <b>CONFIGURABLE TO:</b> 12.5kW 400/50/3 + N + E FUSED AT 20AMPS. 18.5kW 400/50/3 + N + E FUSED AT 32AMPS.  MACHINE SUPPLIED WITH 1.8 METERS OF CABLE.
	<b>Other Services</b> RINSE AGENT HOSE - 2.5 METRE FLEXIBLE. DETERGENT HOSE - 2.5 METRE FLEXIBLE.	<b>Notes</b> <b>** DOOR HEIGHT CAN BE REDUCED TO 2200mm BY ADJUSTING DOOR MECHANISM.</b> APPROX WEIGHTS: EMPTY: 205kg's HEIGHTS MARKED * REPRESENT ±25mm